

DLT-200 Serie

3:1 Phase Uninterruptible Power Supply 6-30kVA



DELTA 200 Series UPS's are, PWM (Plus width modulation) and IGBT technology, microcontroller controlled, sinus waveform output, ONLINE, parallel configurable UPS group.

Technical Specifications

- Output isolation transformer
- 91% efficiency
- Static by-pass
- LCD front panel
- 128 events memory with RTC
- RS232 port provides remote monitoring, remote shutdown
- Custom input and output voltage ranges
- 2 years warranty
- 10 years spare parts support
- CE, TUV, ISO9001, ISO14001 certificates

**True On-line
3 Phase Input
1 Phase Output
6-30 kVA**

Specifications

MODEL	DLT 206	DLT 207	DLT 210	DLT 215	DLT 220	DLT 230
Power	6 kVA	7.5 kVA	10 kVA	15 kVA	20 kVA	30 kVA
INPUT						
Voltage			220/380 Vac (230/400 Vac) 3 phase + Neutral + Earth , +/-15%			
By-pass Voltage			220 Vac, +/- 10%			
Frequency			50 Hz/60 Hz +/- 5%			
EMI			EN62040-2			
Current	3 x 13A	3 X 16A	3 X 21A	3 X 31A	3 X 42A	3 X 62A
Input Voltage Protection			electronic input voltage out of tolerant protection			
OUTPUT						
Power (kW)	4.2	5.25	7	10.5	14	21
Power Factor			0.7			
Voltage			220 Vac (230 Vac) ,Phase + Neutral			
Voltage Tolerance			+/- 1%			
Frequency			50 Hz (60 Hz special product)			
Frequency Tolerance			+/-2% (synchron)			
Efficiency 100% Load			+/- 0,2% (free running)			
THD (Total Harmonic Distortion)			86% (full load)			
Crest Factor			< 3% (linear load)			
Overload Protection			< 5% (non linear load)			
Short Circuit Protection			3:1			
Output Voltage Protection			100%125% load :10 dk			
BATTERY			126%150% load :1 dk			
Type			>150% load : by-pass			
Batteries	20		electronic protection			
Charge Voltage		270 VDC			405 VDC	
Discharge End Voltage		200 VDC			300 VDC	
Battery Cabinet			Standard backup time internal (others external)			
Ambient Temperature			25 C			
Battery Protection			Battery fuse , battery voltage low and high alarm (3 levels)			
Battery Test		Optional			standard automatic every 72 hours	
GENERAL						
Operating Temperature			0 C - 40 C			
Noise Level		< 45 dBA			< 55 dBA	
Protection			IP20			
Altitude			< 2000 m			
Humidity (Non Condensed)			< 90%			
Weight (Without Batteries) (Kg)	106	110	125	130	195	217
Dimensions (mm) HxWxD		950x265x740			1220x500x650	
Interface			Alphanumeric LCD panel, mimic lamps and control buttons			
Communication			RS232+dry contact			
Software			T-Mon UPS Software(3 clients)			
Overtemperature Protection			Electronic overtemperature protection			

